Automatic Transmission Fluid (ATF)

# Adaptive

**DEX III H** 



#### **Product Description**

Goodyear Adaptive DEX III H is an automatic transmission fluid designed to provide superior performance in a wide variety of regular and commercial duty automatic transmissions, including recent General Motors and Ford electronics. It also exhibits outstanding operating characteristics as high performance, anti – wear hydraulic fluid for mobile hydraulic systems

#### **Benefits**

Goodyear Adaptive DEX III H provides the following benefits :

- Friction modifier provides smooth shifting & trouble-free operations
- Enhanced friction durability prolongs the life of transmission life
- Compatible with all types of rubbers, elastomers and metals and provides protection against wear and leakage
- Provides increased Clutch band and Clutch pack capacity
- Excellent thermal stability enables cleaner transmissions
- Excellent low temperature fluidity

#### **Application**

Goodyear Adaptive DEX III H is recommended for service top up of all current General Motors passenger cars and light truck automatic transmissions requiring DEX II & DEX III fluids and all earlier models for which any DEX IIE, DEX II, Type A and all current Ford models where Mercon oils are specified. It is also recommended for all U.S., European and Japanese vehicle transmissions for which DEX III are specified and most U.S., European and Japanese vehicle transmissions for which DEX II or Type A fluids are specified.

Goodyear Adaptive DEX III H is also recommended for use in manual transmissions, transaxles, and power steering systems for which the service - fill product is specified as DEX or Mercon fluids. It may also be used as a wide - temperature range anti-wear hydraulic fluid for many mobile, industrial and marine applications

#### **Properties**

Goodyear Adaptive DEX III H is high performance transmission fluid formulated to provide improved protection on copper and bronze components and to provide smooth operation.

## **Typical Characteristics**

Adaptive	DEX III H
Specific Gravity @ 15°C	0.8525
Flash Point, °C	184
Pour Point, °C	<-40
Viscosity at 40°C, cSt	37.5
Viscosity at 100°C,cSt	7.65
Viscosity Index	181

PERFORMANCE LEVEL- MEETS
Holden HN 2126
Ford Mercon IV
Allison C4
FORD M2C - 138CJ
General Motors Type A Suffix A
Mazda M III Fluid

Typical physical characteristics of Adaptive DEX III H are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

### **Health & Safety**

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from your Goodyear lubricants sales office, or via the Internet on www.goodyearlubricants.me





GOODYEAR LUBRICANTS (MENA) ALONSA ELECTRIC GULF FZCO PLOT NO. S10717, JEBEL ALI, UAE www.goodyearlubricants.me