Semi Synthetic Engine Oil- High Quality

Cruizer

SAE-10W30 / 10W40



API-SN

Product Description

Cruizer is a blend of high quality base stocks and exclusive high performance additive package that ensures minimum wear, extended engine life, longer oil life and easy cold weather starting. It enhances the engine performance and can be used for all high performance gasoline engine cars equipped with direct-injection, multi – valve, and turbo charged technologies, designed to improve the fuel economy efficiency.

Benefits

Cruizer provides the following benefits when used as recommended:

- High fluidity at low temperature and excellent cold start
- · Great durability at high temperature
- Excellent high temperature protection
- Prolong engine life by reducing wear
- Excellent low temperature properties
- Prolonged oil change interval & keeps engine clean
- Protects against rust & wear

Application

Cruizer is suitable for use in passenger cars, 4WDs & light commercial vehicles and is compatible with Petrol/LPG (Dual Fuel), E10, Diesel (without DPF) and most other conventional fuels It provides excellent engine wear protection and therefore enhances engine life.

The special additives added contributes to a significant reduction in engine life. It is perfectly adapted to all vehicles equipped with catalysts using fuel or LPG.

Properties

Cruizer enhances the engine performance and can be used for all high performance gasoline engine cars equipped with direct – injection, multi valve and turbo charged technologies, designed to improve the fuel economy efficiency. It is a Semi Synthetic engine oil specially formulated with refined synthetic base stocks that are suitable for all types of gasoline engines.

GASOLINE 10W30 10W40

PERFORMANCE LEVEL- MEETS

API: SN/SM/SL/SJ/CF Ford WSS M2 C 917 A ACEA: A3/B3/B4

VW 505.01, 505.00, 500.00

Typical Characteristics

Cruizer	10W40	10W30	
API Grade	SN	SN	
Specific Gravity @ 15°C	0.8620	0.8600	
Flash Point, °C	232	228	
Pour Point, °C	- 30	-33	
Viscosity at 40°C, cSt	95.0	75.0	
Viscosity at 100°C, cSt	14.0	11.75	
Viscosity Index	150	150	
Total Base No., Min.	8.50	8.50	
CCS Viscosity cP at -25'C	6250	6200	

Typical physical characteristics of Cruizer are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

Health & Safety

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from your Goodyear lubricants sales office, or via the Internet on www.goodyearlubricants.me





GOODYEAR LUBRICANTS (MENA) ALONSA ELECTRIC GULF FZCO PLOT NO. S10717, JEBEL ALI, UAE www.goodyearlubricants.me